




GAI-M Female connector

Female metric thread (ISO 9974-1) / EO 24° cone end



Series	D1	T1	D3	L1	L2	L3	L4	S1	S2	Weight g/1 piece	Order code*	PN (bar) ¹⁾	
												CF	71
L ³⁾	06	M 10x1.0	4	26.5	19.5	8.0	34	14	14	18	GAI06LM	315	315
	08	M 12x1.5	6	31.0	24.0	12.0	39	17	17	32	GAI08LM	315	315
	10	M 14x1.5	8	32.0	25.0	12.0	40	19	19	39	GAI10LM	315	315
	12	M 16x1.5	10	33.0	26.0	12.0	41	22	22	52	GAI12LM	315	315
	15	M 18x1.5	12	35.0	28.0	12.0	43	24	27	68	GAI15LM	315	315
	18	M 22x1.5	15	37.0	29.5	14.0	46	30	32	111	GAI18LM	315	315
	22	M 26x1.5	19	42.0	34.5	16.0	51	32	36	123	GAI22LM	160	160
	28	M 33x2.0	24	45.0	37.5	18.0	54	41	41	211	GAI28LM	160	160
	35	M 42x2.0	30	51.0	40.5	20.0	62	55	50	459	GAI35LM	160	160
	42	M 48x2.0	36	53.0	42.0	22.0	65	60	60	522	GAI42LM	160	160
S ⁴⁾	06	M 12x1.5	4	33.0	26.0	12.0	41	17	17	35	GAI06SM	400	400
	08	M 14x1.5	5	33.0	26.0	12.0	41	17	19	42	GAI08SM	400	400
	10	M 16x1.5	7	34.0	26.5	12.0	43	22	22	58	GAI10SM	400	400
	12	M 18x1.5	8	35.0	27.5	12.0	44	24	24	70	GAI12SM	400	400
	14	M 20x1.5	10	39.0	31.0	14.0	49	27	27	95	GAI14SM	400	400
	16	M 22x1.5	12	39.0	30.5	14.0	49	30	30	114	GAI16SM	400	400
	20	M 27x2.0	16	45.0	34.5	16.0	56	36	36	189	GAI20SM	315	315
	25	M 33x2.0	20	49.0	37.0	18.0	61	41	46	235	GAI25SM	315	315
	30	M 42x2.0	25	55.0	41.5	20.0	68	55	50	490	GAI30SM	315	315
	38	M 48x2.0	32	59.0	43.0	22.0	74	60	60	597	GAI38SM	250	250