



# METAALUNIE

## Trade & Metal Services v.o.f.


Kreeft 4  
4401 NZ Yerseke (Nederland)  
Postbus 16  
4400 AA Yerseke (Nederland)  
Tel.: +31 (0)113-57 38 78  
Fax: +31 (0)113-57 39 78  
Internet: [www.metalservices.nl](http://www.metalservices.nl)  
E-mail: [info@metalservices.nl](mailto:info@metalservices.nl)

### SMTX Male stud branch tee

Triple-Lok® 37° Flare ends / Male NPTF\* thread (SAE 476)

SAE 070425 MS51512

\*Stainless Steel = NPT to prevent galling



| Tube<br>O.D. |       | Thread<br>NPT/NPTF<br>PT | Thread<br>UN/UNF-2A<br>T | D<br>mm | D1<br>mm | M<br>mm | N<br>mm | Y<br>mm | Weight<br>(steel)<br>g/1 piece | Triple-Lok®<br>Steel | Triple-Lok®<br>Stainless Steel | Triple-Lok®<br>Brass | PN (bar) |     |
|--------------|-------|--------------------------|--------------------------|---------|----------|---------|---------|---------|--------------------------------|----------------------|--------------------------------|----------------------|----------|-----|
| mm           | in.   |                          |                          |         |          |         |         |         |                                |                      |                                |                      | S        | SS  |
| 6            | 3/16  | 1/8-27                   | 3/8-24                   | 3       | 5        | 21      | 18      | 11      | 25                             | 3 STX-S              | 3 STX-SS                       | 3 STX-B              | 420      | 350 |
| 6            | 1/4   | 1/8-27                   | 7/16-20                  | 4       | 5        | 23      | 20      | 11      | 31                             | 4 STX-S              | 4 STX-SS                       | 4 STX-B              | 420      | 350 |
| 6            | 1/4   | 1/4-18                   | 7/16-20                  | 4       | 7        | 27      | 28      | 14      | 49                             | 4-4-4 STX-S          | 4-4-4 STX-SS                   | 4-4-4 STX-B          | 420      | 350 |
| 8            | 5/16  | 1/8-27                   | 1/2-20                   | 6       | 5        | 24      | 20      | 14      | 37                             | 5 STX-S              | 5 STX-SS                       | 5 STX-B              | 420      | 350 |
| 10           | 3/8   | 1/4-16                   | 9/16-18                  | 8       | 7        | 27      | 28      | 14      | 57                             | 6SMTXS               | 6 STX-SS                       | 6 STX-B              | 420      | 350 |
| 10           | 3/8   | 3/8-18                   | 9/16-18                  | 8       | 10       | 29      | 31      | 19      | 77                             | 6-6-6 STX-S          | 6-6-6 STX-SS                   | 6-6-6 STX-B          | 420      | 350 |
| 12           | 1/2   | 3/8-18                   | 3/4-16                   | 10      | 10       | 32      | 31      | 19      | 113                            | 8 STX-S              | 8 STX-SS                       | 8 STX-B              | 420      | 350 |
| 12           | 1/2   | 1/2-14                   | 3/4-16                   | 10      | 14       | 34      | 37      | 22      | 164                            | 8-8-8 STX-S          | 8-8-8 STX-SS                   | 8-8-8 STX-B          | 420      | 350 |
| 14, 15, 16   | 5/8   | 1/2-14                   | 7/8-14                   | 12      | 14       | 37      | 37      | 22      | 173                            | 10 STX-S             | 10 STX-SS                      | 10 STX-B             | 350      | 350 |
| 18, 20       | 3/4   | 3/4-14                   | 1 1/16-12                | 16      | 18       | 42      | 40      | 27      | 272                            | 12 STX-S             | 12 STX-SS                      | 12 STX-B             | 280      | 280 |
| 22           | 7/8   | 3/4-14                   | 1 3/16-12                | 18      | 18       | 46      | 43      | 33      | 323                            | 14 STX-S             | 14 STX-SS                      | 14 STX-B             | 280      | —   |
| 25           | 1     | 1-11.5                   | 1 5/16-12                | 21      | 24       | 46      | 50      | 33      | 413                            | 16 STX-S             | 16 STX-SS                      | 16 STX-B             | 210      | 210 |
| 28, 30, 32   | 1 1/4 | 1 1/4-11.5               | 1 5/8-12                 | 27      | 32       | 52      | 61      | 41      | 681                            | 20 STX-S             | 20 STX-SS                      | 20 STX-B             | 170      | 170 |
|              | 2     | 1 1/2-11.5               | 1 7/8-12                 | 33      | 38       | 54      | 67      | 48      | 905                            | 24 STX-S             | 24 STX-SS                      | 24 STX-B             | 170      | 170 |