



Cylinder accessories → Cylinder mountings; series CM1

AA4 axle




20138183

Fig. 1



Fig. 2



Scope of delivery: pivot pins incl. circlips
1) circlip DIN 471

Part No.	Piston Ø	Ø d 2)	EK e8	EL	L 2)	L6 2)	Standardization	Weight [kg]	Fig.	Note
1823120020	32	20	10	45,2 +0,3	3,5	9	-	0,03	Fig. 1	3) 5)
1823120021	40	22	12	52,2 +0,3	4	9	-	0,05	Fig. 1	3) 5)
1823120022	50	22	12	60,2 +0,3	4	9	-	0,06	Fig. 1	3) 5)
1823120023	63	28	16	70,2 +0,3	4,5	11	-	0,12	Fig. 1	3) 5)
1823120024	80	28	16	90,2 +0,3	4,5	11	-	0,15	Fig. 1	3) 5)
1823120025	100	38	20	110,2 +0,3	5	11	-	0,29	Fig. 1	3) 5)
5236000092	125	34,2	25	132 +0,5	-	3,75	ISO 15552	0,53	Fig. 2	3) 5)
5237000092	160, 200	40,5	30	172 +0,5	-	4,25	ISO 15552	0,99	Fig. 2	3) 5)
5239000092	250	52,6	40	202 +0,5	-	6,75	ISO 15552	2,12	Fig. 2	3) 5)
5239010092	320	59,1	45	222 +0,5	-	7,25	ISO 15552	3,01	Fig. 2	3) 5)
3661302000	25, 32	19	25	29,2	-	2,4	-	0,02	Fig. 2	3) 6)
3661303000	40, 50	21	12	34,4	-	2,8	-	0,03	Fig. 2	3) 6)
3661304000	63, 80	28	16	48,4	-	2,8	-	0,08	Fig. 2	3) 6)
3661306000	100	40	20	58,4	-	3,3	-	0,16	Fig. 2	3) 6)
3661310000	125	40	25	69,4	-	3,8	-	0,3	Fig. 2	3) 6)
3661312000	125, 160	42	30	86,5	-	4,7	-	0,53	Fig. 2	3) 6)
3671312000	160, 200	53	30	93,8	-	5,1	-	0,57	Fig. 2	3) 6)
3661320000	200	60	35	99,5	-	5,2	-	0,84	Fig. 2	3) 6)
2990801302	32	9,6	10	30	-	2,4	-	0,03	Fig. 2	4)
2990801303	40	11,5	12	36	-	2,4	-	0,04	Fig. 2	4)
2990801304	50	15,2	16	48,2	-	2,8	-	0,1	Fig. 2	4)
2990801306	63	19	20	58,2	-	3,3	-	0,16	Fig. 2	4)
2990801310	80	23,9	25	70,2	-	3,3	-	0,3	Fig. 2	4)

- 2) Max.
3) Material: Steel
4) Material: Stainless steel, acid-proof
5) Surface: galvanized
6) Surface: nitrocarburized



METAALUNIE

Trade & Metal Services v.o.f.

Kreeft 4
4401 NZ Yerseke (Nederland)
Postbus 16
4400 AA Yerseke (Nederland)
Tel.: +31 (0)113-57 38 78
Fax: +31 (0)113-57 39 78
Internet: www.metalservices.nl
E-mail: info@metalservices.nl

Cylinder accessories → Cylinder mountings; series CM1

AA4 axle

Part No.	Piston Ø	Ø d 2)	EK e8	EL	L 2)	L6 2)	Standardiza- tion	Weight [kg]	Fig.	Note
2990601312	100	28,6	30	86,5	-	4,6	-	0.3	Fig. 2	4)
2990601313	125	28,6	30	94,5	-	4,6	-	0.58	Fig. 2	4)
2990601320	160	33	35	99,5	-	5,1	-	0.83	Fig. 2	4)

2) Max.

3) Material: Steel

4) Material: Stainless steel, acid-proof

5) Surface: galvanized

6) Surface: nitrocarburized